



Lubrificante EasyLube Elite



Engineered to meet the most demanding requirements, replaces labor intensive regreasing jobs, prevents unnecessary maintenance repairs and increases bearing reliability.

Easylube® Elite (version 5.0) model is equipped with electromechanical gear set and Bicolor LED warning light.

Bicolor LED warning light provides information about bearing conditions for maintenance personnel through visual inspection.

LUBRICATION SPECIFICATIONS

Material Outlet: 1/2" PT (M);

Dispensing Grease Volume: 60 ml, 150 ml, 250 ml;

Dispense Period Setting: 1 to 12 months Adjustable;

Operating Temp. Range: -20 to 60°C (-4 to 140°F);

Output Pressure (Exit cup): 75 - 150 psi (5 - 10 bar); Self-Adjust to back pressure;

Dimensions (Stature x Diameter):

* 13.9 x 8.9 cm (5.47 x 3.5");

* 16.3 x 8.9 cm (6.4 x 3.5");

* 19.6 x 10.2 cm (7.7 x 4");

Electrical Ratings: P-613B Anti-explosive Li-battery pack: DC 6 Volt, UL94-V0 Flammability Rating;

Replaceable Grease Cartridge:

* 60 Elite:

> ES-60-1000-3B;

> ES-60-1500-3B;

> ES-60-2000-3B;

> ES-60-5000-3B;

* 150 Elite:

> ES-150-1000-3B;

> ES-150-1500-3B;

> ES-150-2000-3B;

> ES-150-5000-3B;

* 250 Elite:

> ES-250-1000-3B;

> ES-250-1500-3B;

> ES-250-2000-3B;

> ES-250-5000-3B;

* or DIY filled with grease by your selection;

UL Approved in Hazardous Location:

* File E218441;

* Class I Division 2 Group B, C, D;

* Class II Division 2 Group F, G;

* Class I, Zone 2, Group IIB T5; Zone 22, T5;

CE Certificate:

* EC Council Directive 2004/108/ EC;

* TÜV Registration No. AE5016 95430001;

CNEx Certificate:

* CQST approved in hazardous locations :

> Ex icIIBT5 Gc , ExicD22 T95;

> Cer. No. : CNEx13.3279X;

Ingress Protection: IP65;